

# GENERAL CHARACTERISTICS OF THE TANK CONTAINERS



Travessera de Can Estapé, 5-7. Pol. Ind. Can Estapé 08755 Castellsbisbal (Barcelona)  
Tel. 93.708.96.00 – Fax: 93.708.96.01  
[www.contank.com](http://www.contank.com) e-mail: [contank@contank.com](mailto:contank@contank.com)

## MULTICOMPARTMENT TANKS CAPACITY OF 32.000 L.

Range CTKU323

### General characteristics of the tank:

Type.....	ADR / RID
External dimensions:	
Length .....	9.128 mm 30 feet
Width.....	2.500 mm
Height.....	2.670 mm
Maximum Gross Weight.....	34.500 Kg.
Tare weight (approx.).....	4.950 Kg.
Total capacity of tank.....	32.000 l
Number of compartments.....	3 (9.500 / 13.000 / 9.500)

Thermal insulation: fibreglass (50 mm) and polyurethane plate (50 mm). Covering of stainless steel AISI 304.

Heating: By serpentine of stainless steel AISI 304. Maximum working pressure: 3 bar. Hydrostatic test pressure: 4.5 bar. Steam trap at the exit.

Multimodal tank designed to transport products of classes 3, 4.1, 5.1, 6.1 and 8 of ADR and RID.