

GENERAL CHARACTERISTICS OF THE TANK CONTAINERS



Travessera de Can Estapé, 5-7. Pol. Ind. Can Estapé 08755 Castellsbisbal (Barcelona)
Tel. 93.708.96.00 – Fax: 93.708.96.01
www.contank.com e-mail: contank@contank.com

SPECIAL CONTAINERS (high temperature)
CAPACITY OF 33.500 L.

Range CTKU331

General characteristics of the tank:

Type.....	ADR, RID and IMO
External dimensions:	
Length	7.820 mm 25 feet
Width.....	2.600 mm
Height.....	2.670 mm
Maximum Gross Weight.....	36.000 Kg.
Tare weight (approx.).....	4.600 Kg.
Total capacity of tank.....	33.500 l
Number of compartments.....	1 With 4 wave breaks

Reinforced heating: Reinforced thermal insulation: 2 layers of rock wool totalling 110 mm. Cladding: 2 mm. thick glass-reinforced polyester. Non-slipping aluminium plate placed between top spill boxes with internal metal supports.

Thermal insulation: Steam coil with 7 channels along the whole length of the shell on the bottom of the tank, "T" channel in the front head and additional channel through bottom discharge box. ½ steam traps at the outlets. Maximum working pressure 10 bar (184°C).

Multimodal tank designed to transport products of classes 3, 4.1, 4.2, 5.1, 6.1, 8 and 9 of ADR/RID and IMDG (IMO 4).