

GENERAL CHARACTERISTICS OF THE TANK CONTAINERS



Travessera de Can Estapé, 5-7. Pol. Ind. Can Estapé 08755 Castellsbisbal (Barcelona)
Tel. 93.708.96.00 – Fax: 93.708.96.01
www.contank.com e-mail: contank@contank.com

STANDARD CONTAINERS

CAPACITY OF 17.500 L.

Range CTKU175

General characteristics of the tank:

Type.....	ADR and RID.
External dimensions:	
Length.....	6.058 mm 20 feet.
Width.....	2.438 mm
Height.....	2.591 mm
Maximum Gross Weight.....	30.480 kg.
Tare weight (approx.).....	3.625 kg.
Total capacity of tank.....	17.500 l
Security handrail	Yes
<u>Material:</u>	
Number of compartments.....	1
Maximum work pressure.....	3 bar
Hydraulic test pressure.....	4,5 bar
Construc. Mini thickness F/H.....	5,2 mm
Construc. Mini thickness V/S.....	4,8 mm
Eq. thickn. Mild steel.....	6,35 mm

Equipment:

Bottom discharge.....	Yes
Number of closures in series.....	3
Top discharge.....	Yes
Number of closures in series.....	2
Relief valves.....	1
Setting.....	3,75 bar
In series.....	Yes
Rupture discs.....	1
Setting.....	4,15 bar

Multimodal tank designed to transport products of classes 3, 5.1, 6.1, 8 and 9.