

GENERAL CHARACTERISTICS OF THE TANK CONTAINERS



Travessera de Can Estapé, 5-7. Pol. Ind. Can Estapé 08755 Castelbisbal (Barcelona)
Tel. 93.708.96.00 – Fax: 93.708.96.01
www.contank.com e-mail: contank@contank.com

STANDARD CONTAINERS

CAPACITY OF 35.000 L.

Range CTKU351

General characteristics of the tank:

Type.....	ADR, IMO and RID.
Material of tank	Stainless steel 316 Ti
External dimensions:	
Length.....	7.820 mm 25 feet.
Width.....	2.438 mm
Height.....	2.591 mm
Maximum Gross Weight.....	35.000 kg.
Tare weight (approx.).....	4.400 kg.
Total capacity of tank.....	35.000 l
Number of compartments.....	1 with 4 wave breaks
External thermometer.....	1 in bottom of the tank (0° at 120 °C)
Security handrail.....	Yes

Thermal insulation: 1 layer of glass wool with 150 mm total thickness. Clad: 2 mm thick glass reinforced polyester.

Reinforced heating: steam coil with 4 channels, manometer, ball valve and 1" BSP threaded connection at the inlet.
Maximum working pressure: 4 bar (-20 at 100 °C).

Multimodal swap tank designed to transport products of classes 3, 4.1, 4.2, 6.1, 8 and 9.